

Ultra Filter Single Stage

Drinking Water System

Filter Instructions



STEP 1: Turn off cold water shut-off valve to the Filter System.

STEP 2: Turn cartridge counter-clockwise until unit releases. Gently pull down to remove from head. Discard used cartridge.

Notice: Place a bucket or pan under system to catch any water drips

STEP 3: Hold new cartridge with label slightly facing left. The two nozzles on top of cartridge should be toward the back of the Filter System, and the two extended flanges should be out to each side.

STEP 4: Lift cartridge straight up into the manifold until the two nozzles seat into the manifold ports, and the two extended flanges are flush with the manifold.

STEP 5: Turn cartridge clockwise until it stops.

STEP 6: Turn on cold water shut-off valve and faucet. Check for leaks.

STEP 7: Pressure test and purge per **Step 6**.

IMPORTANT NOTE: We highly recommend you periodically check for leaks at least 48 hours after performing a filter change. Placing a baking sheet lined with some paper towels under the system for a few days allows you to quickly see if any problems develop. If a leak appears, please unscrew and then reattach your new filters using the process documented above. If the problem persists, please contact our Customer Support Department at **877-534-5837 x5**. After a filter change, it is normal for your water to appear milky or cloudy. Additionally, some small particulates (called filter fines) may appear. *These effects are NOT harmful to you, your family or the system.* Your water will return to normal within a few days once the filters have fully purged all the air out of the system.